

# FINPRO 2K THINNERS



## THINNING SOLVENT FOR 2K COATINGS

Finseal 2K Thinners is used for thinning VULK Finseal PU HD Polyurethane and Finseal PA Polyaspartic coatings.

4L

### DIRECTIONS FOR USE

Finpro 2K Thinners is a specially formulated solvent based thinner used for viscosity reduction in solvent based coatings Finpro PA and Finpro PU HD.

Standard reducer for use in application temperature ranges of 18 – 27°C

### APPLICATION DIRECTIONS

Add Finpro 2K Thinners to the freshly mixed Finduro polyurethane or polyaspartic coating system at 5% by volume (10% maximum) to reduce application viscosity.

Mix thoroughly using a low-speed mechanical mixer. Apply the coating by roller or squeegee.

### DO NOT SMOKE.

Keep container closed when not in use.  
Avoid breathing the vapour, or  
Unnecessary skin contact.

Refer to Safety Data  
Sheet before use

**POISON**

KEEP OUT OF REACH  
OF CHILDREN

### IMPORTANT

Read and follow manufacturer's directions when thinning coatings.

### HAZARDS

Keep away from all sources of ignition – DO NOT SMOKE.

Harmful by inhalation, including contact with skin and if swallowed. Irritating to eyes, respiratory system and skin. Avoid contact with eyes. Avoid contact with skin. Avoid breathing vapour or spray mist.

Dispose of contents and container in accordance with all local, regional, national and international regulations.

### FIRST AID

If swallowed DO NOT induce vomiting. Give a glass of water.

If poisoning occurs, contact a doctor or Poisons Information Centre (Ph. 131 123). If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

If in eyes, hold eyes open, flush with water for at least 15 minutes and see a doctor if irritation persists.

### DANGER

This package contains volatile and flammable solvents and when using contents adequate ventilation to the outside must be provided.

All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches, etc.) must be eliminated in, or near the working area.



PAINT  
UN 1263  
CLASS 3 PACKING GROUP III  
HAZCHEM CODE •3Y

### DISCLAIMER / STATEMENT OF RESPONSIBILITY

Purchase or use of the product referred above ('the Product') constitutes acceptance of these terms. Any information provided by Vulk Pty Ltd ('Vulk') is of a general nature and should not be taken as advice and is, to the extent permitted by law, provided without warranty as to the accuracy, reliability or completeness of that information. Further, no warranty is provided in respect to the quality, suitability or fitness for purpose of the Product. Expert advice should be taken in respect to any use of the Product. So far as is

permitted by law, any party purchasing or using the Product indemnifies Vulk against and releases Vulk from any claim, liability, loss, cost or similar directly or indirectly arising out of the supply or use of the Product or this technical data sheet. Vulk's liability to any party is limited to cost of replacement or repair of the Product and is reduced proportionately to the extent that an act or omission of any other party contributes to the liability.

VULK.COM.AU

enquiries@vulk.com.au

5 Piping Lane, Lonsdale SA 5160

Phone: 1300 069 388 / 08 7129 6955

**VULK**

AUSTRALIA'S LEADING CONCRETE FLOORING CENTRE

VULK TDS Issue February 2026 Ver FPPUHD.001

HYDROC

MIRAFLOOR

FINDURO

AARDCURE